



BRACED WALL PANEL LEGEND
 SEE BUILDING CODE FOR PROPER TIE DOWNS UDC COMM 21.25

	BP-1 METHOD 4 48" PANEL FOR CONTINUOUS SHEATHING
	METHOD 7 (BP-2) REDUCED PANEL FOR CONTINUOUS SHEATHING
	BP-3 METHOD 6 GYPSUM INTERIOR PANEL
	BP-4 METHOD 9 POSTAL FRAMING PANEL
	BP-5 METHOD 5 VERTICAL & HORIZONTAL WALL LINES

NOTE:

1. STRUCTURAL PANEL WALL SHEATHING SHALL BE 7/16" OSB (MIN) WITH A STUD SPACING OF 16" O.C. (MAX.)
2. WALL SHEATHING SHALL BE INSTALLED WITH 8d NAILS AT 6" O.C. AT EDGE/PERIMETER AND 12" O.C. AT ALL INTERMEDIATE SUPPORTS/STUDS
3. PROVIDE (2) ANCHOR BOLTS INSTALLED PER COMM 21.16 AT EACH REQUIRED PANEL.

SECOND FLOOR PLAN

SCALE: 1/4"=1'-0"

FIRST FLOOR PLAN

SCALE: 1/4"=1'-0"

